LPR / VUR

Lomanco offers two styles of Aluminum Ridge Vents—the LPR and VUR. The LPR Ridge Vent is available in 8' or 10' sections and is adjustable to fit 3/12 to 12/12 roof pitches. The VUR Ridge Vent is available in 10' sections and is adjustable to fit 3/12 to 8/12 roof pitches.

Features—Lomanco LPR and VUR Ridge Vents are made of embossed aluminum finishes for added strength, extended paint life, and blending appearance with shingles. Both offer a high Net Free Area—18 square inches of NFA per foot.

Installation—The LPR and VUR are manufactured with pre-notched nail holes for easy installation. Both are one-piece construction and can be cut

Available Colors

at desired length at two-foot intervals. Hurricane straps and tight fitting, high density polyethylene foam end-plugs are available for both the LPR and VIIR



Texas Department of Insurance "Windstorm" Approved



Low profil	e	blends	with	roof
construct	o	n.		

- Large 2-inch-wide nailing flange.
- Easy installation, male/female connections—no straps necessary.
- ▶ Optional strap available in all colors.
- LPR has an aerodynamic design revolutionary three-baffle system for complete weather protection.

Model	Section LTH.	Net Free Area (in. ²)
LPR-8*	8	144
LPR-10*	10	180
VUR-10*	10	180
V-Plug	_	_
L-Plug	_	_

LPR and VUR hurricane straps are available



VUR Only

- Easy installation, male/female connections—no straps necessary.
- ▶ Engineered weather infiltration protectors at each connection.
- Exterior wind baffles.

